

# PNEUMATIC SEALLESS STRAPPING TOOLS FOR STEEL STRAP

## ST-INCA 13-16-19 STD

### FLAT SURFACES PNEUMATIC SEALLESS STRAPPING TOOL FOR STEEL STRAP



CHART OF TYPES

MODEL	ITEM.NO.	WIDTH	SPEED
ST-INCA 13 STD 2000 N	106.130.310	13 mm 1/2"	11 mt/m
ST-INCA 13 STD 3500 N	106.130.410	13 mm 1/2"	7 mt/m
ST-INCA 16 STD 3500 N	106.160.410	16 mm 5/8"	7 mt/m
ST-INCA 16 STD 5500 N	106.160.510	16 mm 5/8"	5 mt/m
ST-INCA 19 STD 3500 N	106.190.410	19 mm 3/4"	7 mt/m
ST-INCA 19 STD 5500 N	106.190.510	19 mm 3/4"	5 mt/m

#### TECHNICAL DATA

Strap quality	standard Rmax. 850N/mm <sup>2</sup>
Joint type	sealless
Package type	flat (min. lenght 200 mm / 8")
Strap width	13-16-19 mm / 1/2" - 5/8" - 3/4"
Strap thickness	from 0.4 up to 0.6 mm / 0.016" - 0.024"
Max tension	2000 N/440 lbs 3500 N/770 lbs 5500 N/1200 lbs
Max tension speed	11 - 7 - 5 mt/min / 36 - 23 - 17 ft/min
Air pressure	from 5.5 upto 6.5 bar max / 78 - 92 PSI
Air consumption	12 l/s - 25 cu ft/min
Weight	around 7 kgs / 15.4 lbs

## ST-INCA 13-16-19 HT

### FLAT SURFACES PNEUMATIC SEALLES STRAPPING TOOL FOR STEEL STRAP



CHART OF TYPES

MODEL	ITEM.NO.	WIDTH	SPEED
ST-INCA 13 HT 3500 N	113.130.410	13 mm 1/2"	7 mt/m
ST-INCA 13 HT 5500 N	113.130.510	13 mm 1/2"	5 mt/m
ST-INCA 16 HT 5500 N	113.160.510	16 mm 1/2"	5 mt/m
ST-INCA 19 HT 5500 N	113.190.510	19 mm 3/4"	5 mt/m

#### TECHNICAL DATA

Strap quality	standard & high tensile Rmax. 1100N/mm <sup>2</sup>
Joint type	sealless
Package type	flat (min. lenght 200 mm / 8")
Strap width	13-16-19 mm / 1/2" - 5/8" - 3/4"
Strap thickness	from 0.4 up to 0.63 mm / 0.016" - 0.025"
Max tension	3500 N/770 lbs 5500 N/1200 lbs
Max tension speed	11 - 7 - 5 mt/min / 36 - 23 - 17 ft/min
Air pressure	from 5.5 upto 6.5 bar max / 78 - 92 PSI
Air consumption	12 l/s - 25 cu ft/min
Weight	around 9 kgs / 19.8 lbs