

BATTERY STRAPPING TOOLS FOR PP/PET STRAP

DIGIT SMART LXT

FLAT AND ROUND SURFACES BATTERY STRAPPING TOOL FRICTION WELD SEAL



TECHNICAL DATA

Strap quality	PP/PET
Joint type	friction weld seal
Package type	flat (min. 120 mm - 5") round surface (min. diam. 700 mm - 28")
Strap width	10-13-16 mm / 3/8" - 1/2" - 5/8"
Strap thickness	from 0.5 up to 1.0 mm / 0.019" - 0.038"
Max tension	2300 N - 506 lbs
Max tension speed	around 12 mt/min - 39,33 ft/min
Battery	Makita 14.4 Vdc - 3.0 Ah Li-ion
Weight	around 3,8 kgs / 8.3 lbs (battery included)

CHART OF TYPES

MODEL	ITEM.NO.	STRAP WIDTH
DIGIT SMART LXT	127.990.810	10-16 mm 3/8"-5/8"



Recharger for Li-ion Battery



New digital adjustment system for tension and sealing time



ITEM NO. 291.336.400

Inox plate protection for Digit LXT, SMART, POWER



Li-ion Battery

- High capacity
- No memory effect
- Light and compact
- Built-in memory chip