

## POLI 10-19 LT



CHART OF TYPES

MODEL	ITEM.NO.	STRAP WIDTH
POLI10LT	109.100.310	10-11 mm 3/8"
POLI13LT	109.130.310	12-13 mm 1/2"
POLI16LT	109.160.310	16 mm 5/8"
POLI19LT	109.190.310	19 mm 3/4"

### FLAT AND ROUND SURFACES PNEUMATIC STRAPPING TOOL FRICTION WELD SEAL

#### TECHNICAL DATA

<b>Strap quality</b>	PP/PET
<b>Joint type</b>	friction weld seal
<b>Package type</b>	flat / round (min. diameter 700 mm / 28") opt. round pack. base kit min. 500 mm / 20"
<b>Strap width</b>	10-13-16-19 mm / 3/8"- 1/2"- 5/8"- 3/4"
<b>Strap thickness</b>	from 0.4 up to 0.9 mm / 0.016" - 0.035"
<b>Max tension</b>	2500 N - 555 lbs (adj. by clutch system)
<b>Max tension speed</b>	around 11 mt/min - 36 ft/min
<b>Air pressure</b>	from 5.5 upto 6.5 bar max / 78 - 92 PSI
<b>Air consumption</b>	12 l/s tension - 14 l/s welding /29 cuft/min
<b>Weight</b>	around 4,9 kgs / 10.8 lbs

## POLI 13-19 MT



CHART OF TYPES

MODEL	ITEM.NO.	STRAP WIDTH
POLI13MT-clutch	115.130.710	12-13 mm 1/2"
POLI16MT	115.160.710	16 mm 5/8"
POLI19MT	115.190.710	19 mm 3/4"

### FLAT AND ROUND SURFACES PNEUMATIC STRAPPING TOOL FRICTION WELD SEAL

#### TECHNICAL DATA

<b>Strap quality</b>	PP/PET
<b>Joint type</b>	friction weld seal
<b>Package type</b>	flat / round (min. diameter 700 mm / 28") opt. round pack. base kit min. 500 mm / 20"
<b>Strap width</b>	13-16-19 mm / 1/2"- 5/8"- 3/4"
<b>Strap thickness</b>	from 0.6 up to 1.27 mm / 0.024" - 0.050"
<b>Max tension</b>	3500 N - 770 lbs (adj. by clutch system-opt.)
<b>Max tension speed</b>	around 9 mt/min - 30 ft/min
<b>Air pressure</b>	from 5.5 upto 6.5 bar max / 78 - 92 PSI
<b>Air consumption</b>	12 l/s tension - 14 l/s welding /29 cuft/min
<b>Weight</b>	around 5,2 kgs / 11.4 lbs